

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
J										SIDE	DATE	DESCRIPTION		APPROVER	J
I										△					
H										△					
G															
F															
E															
D															
C															
B															
A															

P.C.B. PLYOUT

一. MATERIAL:

- 1.Insulator:PBT+30%Glass Fiber (UL94V-0)
- 2.Contact:Brass
- 3.Contact Plated:Gold Flash over Tin Or Glod Plated Or Tin Plated
- 4.Shell:Steel,Nickel Plated

二. SPECIFICATION?

- 1.Current Rating:5 AMPS
- 2.Insulation Resistance: 5000M_i, MIN. At 500VDC
- 3.Dielectric Strength: 500V for One minute
- 4.Operation Temperature: -55° C~+105° C.

电话(tel)			公差				
传真(fax)			0±0.25 00±0.20 000±0.05	0'±1.0' 00'±0.5' 000'±0.1'			
比例(scale)	1 : 1	日期 (date)		单位(units)	mm	图 名(name)	DR9P/M 叉锁 4.8
页次(sheet)	A / 1	绘图 (draw)	唐	颜色 (shaded)		图号(draw number)	DRCS09M
版次(rev.)	A / 0	审核 (ch'k)	唐	材料(mt'l)		料号 (Part number)	DRCS09M
视图(view)		核准(app'd)	林	处理(finish)	伍	业务咨询电话	